

## [CF Series] Loose Radial Lead Cutting Equipment

### CF-360 散裝電容剪腳機 Loose Radial Lead Cutter

電壓 Power: 110V/220V AC 50/60Hz

尺寸 Dimension: 500mm (L), 430mm(Width), 470mm(H)

淨重 Weight: 24 Kgs

毛重 Shipping weight: 27kgs.




CF-360

CF-360X



- 採平面送料，手放大小零件皆適用。Linear Feeding on trail is suitable for most parts.
- 可依產量、場地擴充購買自動送料盤和送料機組。 Upgradable to CF-366, add bowl feeder or worktable
- 特殊切斷法，刀具壽命長。 Durable cutters from unique cutting method.
- 光纖計數，設定準確(計數器屬選配) Optical LED Component Counter is optional accessory. (CF-360)
- 調整簡單，操作簡便，保養容易。 Easy maintenance and simple operation.



	A	本體長度 Body Length	3 - 25 m/m
	H	腳長 Lead Length	3 - 20 m/m
	W	線徑 Wire diameter	0.4 - 2.0 m/m
加工量 Working Capacity			150pcs/ Min

### CF-366 自動散裝電容剪腳機

#### Automatic Loose radial Lead Cutter

電壓 Power: 110V/60HZ or 220V/50HZ

空壓 Air Source: 4 kgs/cm<sup>2</sup>

尺寸 Dimension: 1150mm (L), 700mm(Width), 1050mm(H)

淨重 Weight: 145 Kgs

加工量 Capability: 18,000pcs/Per hour

- 適合大量生產、短腳作業的最佳輔助設備。 Shorten leads in massive production.
- 切腳機組與振動送料機組可分開或合併使用。 Cutter can operate independently from bowl feeder and table.

#### 型號 Models:

##### 1. Specialized Single Function 單一零件功能-

Models	適用元件型狀 Available shapes	尺寸範圍(mm)	圖例	
CF-3661	圓柱形狀 Cylindrical parts 	(Dia.* H) 4 *8~* 10*20	Condenser, Electrolytic cap. LED	<p>CF-3661</p>
CF-3662	方體零件 Cuboids parts 	(L*H*T) 3*3*3 ~25*15*8	Power transistor TO220, LED, Mila	<p>CF-3662</p>
CF-3663	扁圓零件 Oblate parts 	(Dia.*Thickness) 4*3 ~ 18*6	Film cap., Ceramic cap. Poly cap.	<p>CF-3663</p>

##### 2. Multifunction 多功能 - CF-366 =CF-3661+CF-3662+CF-3663



CF-366X



CF-366