

# RF-101 電阻成型機—M 及 C 型 Axial Lead Former M&C Type

- 電壓 Power: 110/220 V AC. 60/50HZ
- 尺寸 Dimension: 1050(L), 600(W), 650(H)mm
- 重量 Weight: 115 Kgs.

RF-101-M、RF-101-C

( M=MA+MB, C=CA+CB)

適用於帶式及散裝零件 For both loose and tape packed components.

 <p>Model RF-101-M</p>	A	本體長度 Body length	3.8~20.0 mm
	B	本體大小 Body diameter	2.3~8.0 mm
	C	肩距 Shoulder	1.2 Min
	D	高度 Height (Critical)	8 mm. Fixed at certain parameter
	E	腳長 Lead length	Adjustable
	S	支持點 Supporting point	2~3 mm
	L	兩腳寬度 Pitch	A + 2C
	W	線徑 Wire diameter	Ø0.4~ Ø1.3
	加工量 Capacity		110 pcs/Min


 <p>Model RF-101C</p>	A	本體長度 Body length	3.8~20 mm
	B	本體大小 Body diameter	2.3~8 mm
	C	肩距 Shoulder	1.2 Min
	D	高度 Height (Critical)	8 mm. Fixed at certain parameter
	E	腳長 Lead length	Adjustable
	F	Punching Height	2 mm (Fixed)
	S	支持點 Supporting point	W + 0.4~0.5 mm
	L	兩腳寬度 Pitch	A + 2C
	L	線徑 Wire diameter	Ø0.6~ Ø1.3
加工量 Capacity		110 pcs/Min	

RF-101-MA、RF-101-CA

適用於散裝零件 For reel/tape packed components

RF-101-MB、RF-101-CB

適用於帶式零件 For loose packed components



Smashing



RF-101 M <http://www.youtube.com/watch?v=jjZj81D2pjA>